

UVX-300G-REM

COMPACT LUMINESCENCE SENSOR


Confirm manufacturing processes more reliably than vision systems that cost ten times more. The UVX employs our field-proven, patented technology, for effective detection of UV luminescent materials such as wood, grease, adhesives, UV inks and optical brighteners used in many industrial applications. Its high-sensitivity and fast response makes the UVX suitable for high-speed automation processes and long-range use. The small optical head allows use in space-constrained applications. The metal alloy case and glass lens provide robust construction expected in an industrial environment.

The UVX features a 2-digit display that provides an indication of signal strength making set-up and integration quick and easy. The versatile sensor provides user set-up parameters including light source intensity adjustment, detection threshold and gain selection making the UVX useful in a wide range of applications.

The UVX includes both a discrete PNP/NPN output and an analog output. The discrete output is automatically set for PNP or NPN operation. The analog output signal may be used to access the relative quantity of UV materials such as optical brightener coatings applied to clear films.

UVX





Applications

- Adhesives, gums and glues
- Labels, packaging
- UV inks, visible and invisible
- UV crayons and chalk, lumber marking
- Tamper-evident-seals
- Textiles, luminescent threads
- Optical brightness, paper industry
- Grease and oils

Design & Features

- Small optical head
- Small spot size
- High sensitivity and high resolution
- Fast response
- Display range 00-99
- Five gain settings
- Analog output
- PNP/NPN discrete output

Ordering Information



UVX-300G-REM
Luminescence sensor with
remote sensing head

Accessories



UVX-300B
Bracket



UVX-300C
Cable 5P, 5M, M12, F



UVX-300SB
Sensor bracket

NOT INTENDED FOR USE IN
PERSONAL SAFETY APPLICATIONS.

Functions

NORMAL OPERATING MODE
SENSITIVITY THRESHOLD
UV LED INTENSITY
HYSTERESIS LEVEL
DISCRETE OUTPUT
OUTPUT PULSE STRETCH
SECURITY
TEACH MODE

Displays relative reflection intensity
x1, x2, x3, x4, x5
Set detection level
Set LED, LO, MED, HI
Set undetect level 1-9 steps below threshold
Set normally open or normally closed
Set minimum output period 10...90ms
Lock/unlock pushbutton controls
Auto-set detection threshold

Specifications

Light source	370nm UV LED, 100,000 hrs.	Indicators	LED
Light spot size	6...8mm dia. @ 50mm	7-Segment display	Power
Light source intensity	3 levels	Green LED	Detect
Sensing distance	up to 300mm	Red LED	Program
Receiver Spectral Response	350...1000nm	Yellow LED	
Response time	<150µs	Connector M12	
Switching Frequency	6kHz	Pin 1	Power 10 to 24VDC
Relative intensity display range	00 to 99	Pin 2	Discrete output PNP/NPN NO/NC
Sensitivity	x1, x2, x3, x4, x5	Pin 3	Ground
Signal level	Two 7 segment digits	Pin 4	Analog output 0 to 5V DC
Detection threshold	Two 7 segment digits	Pin 5	Remote LOCK/ UNLOCK input
Digital Output	Auto-Detect PNP / NPN		
Output Function	NO/NC selectable		
Analog Output	0...5V		
Power indicator	Green LED		
Detect indicator	Red LED		
Programming indicator	Yellow LED		
Data retention	EEPROM non-volatile memory		
Dimensions (control)	51mm x 61mm x 25mm (2.0" x 2.4" x 1.0")		
Dimensions (sensor head)	30mm x 18mm x 20mm (1.2" x 0.7" x 0.8")		
Cable length (sensor head)	1m (40")		
Weight	95 g (0.21 lbs.)		
Supply Voltage	24 VDC		
Operating Current	60 mA		
Short Circuit Protection	Discrete output		
Overload / Reverse Polarity Protection	Supply voltage		
Operating temperature	-20°C...55°C		
Storage temperature	-20°C...70°C		
Housing	Metal alloy		
Mechanical Protection	IP65 NOT FOR PRESSURE WASHDOWN		



WARRANTY EMX INC. the product described herein for a period of 2 years under normal use and service from the date of manufacture. The product will be free from defects in material and workmanship. This warranty does not cover ordinary wear and tear, abuse, misuse, overloading, altered products, or damage caused by the purchaser from incorrect connections, or lightning damage. There is no warranty of merchantability. There are no warranties expressed, implied or any affirmation of fact or representation which extend beyond the description set forth herein. EMX Inc. sole responsibility and liability, and purchaser's exclusive remedy shall be limited to the repair or replacement at EMX's option of a part or parts not so conforming to the warranty. In no event shall EMX Inc. be liable for damages of any nature, including incidental or consequential damages, including but, not limited to any damages resulting from non-conformity defect in material or workmanship.

MADE IN THE USA

©EMX Industries, Inc. all rights reserved. REV 2.112/4/12